



**Best Products, Best Prices, Best Service
CASE CLOSED!**



MeltMate® Hot Melt Gear Pump System

State of the Art Features

The MeltMate® is durable, light weight and can easily be located in any production area quickly. Just plug into 120V power and add glue! The machine has adjustable RTD sensor temperature control from 100°-400°F (38°-200°C) enabling the customer to use low temp or regular adhesive. Unit has tank and hose fault notification, as well as, over temperature protection.

Flexible and Upgradable

The MeltMate® is extremely versatile to fit most customer applications with one simple unit. The Meltmate® accommodates one hose with either manual handgun or automatic gun operations. Automatic head can be either electric or pneumatic depending on your individual application. This flexibility allows the operator to use the system with a handgun and easily switch to an automatic head as production increases.

Maintenance Friendly

Teflon® coated tank reduces char and build up that will affect production. The precision gear pump and 28 RPM motor will provide continuous supply of hot melt under the most difficult conditions. Easy, accessible electronics, motor and pump

Features of the Melt Mate® Gear Pump System

- Manual or Automatic operation
- 10 lb adhesive capacity
- Precision gear pump
- Adjustable temperature control
- Tank temperature range 100°-400°F
- Accommodates low temp or standard hot melt
- Flow control valve
- Flexible 120V power
- 120 Ohm Nickel RTD controlled temperature
- Teflon® coated tank
- Tank sensor fault alert
- Hose sensor fault alert
- Tank over temp protection
- Motor run ready light
- Single hose
- Accommodates handgun, pneumatic or electric head (Slaved)
- Extrusion or spray handgun
- Bottom or top mount handgun
- High flex hose standard
- Stainless Steel construction
- Easy access components
- Lightweight
- Available with rolling cart for instant set up
- Boom and balancer available
- Glue pattern controller available
- Can be shipped via UPS or FEDEX

MADE IN THE U.S.A.

MeltMate® Specifications

Tank Capacity:	10 lbs/4.5 Kg
Weight:	45 lbs/20.5 Kg
Temp. Range:	100°-400°F/38°-200°C
Temp. Control:	RTD Ni 120 Ohm
Power:	120 VAC
Dimensions:	14" L x 21" H x 13" W
Motor:	1/6 HP, 28 RPM
Pump Rate:	44 lbs/20 Kg per Hour
Melt Rate:	8 lbs per Hour
Hoses:	One, 16 foot length max.
Heads:	Handgun or Automatic
Options:	Spray/Swirl Handguns, Foot Pedal, Boom & Balancer and Rolling Cart

Keystone Industries® • 140 Manufacturers Court, Winder, GA 30680

(800) 235-8090 • (770) 586-5990 • FAX: (770) 586-5991 • www.keystoneparts.com • sales@keystoneparts.com